



SIZE A (B)	L	H ABOUT	d	$\phi$	D1	④ GASKET	WEIGHT (kg)	Q'ty	REMARKS
10 (3/8)	65	53	15	33	26	$\phi 30.5 \times \phi 22.5 \times t 3.2$	0.4		
15 (1/2)	80	62	18	45	32	$\phi 33 \times \phi 24.5 \times t 3.2$	0.6		
20 (3/4)	90	70	23	50	38	$\phi 39 \times \phi 30.5 \times t 3.2$	0.8		
25 (1)	110	87	30	60	46	$\phi 51 \times \phi 40.5 \times t 3.2$	1.5		

※SIZE 8A can respond by using bushing.

USER	
NAME	Y-TYPE STRAINER
MODEL	Y800WCBS-H
SIZE	SEE BELOW LEFT
CONNECTION	Rc
MAX. PRESSURE	800Lb RATING
MAX. TEMPERATURE	(MAX. 350°C)
TEST PRESS. (WATER)	20.6 MPaG
TEST PRESS. (AIR)	—

Allowable differential pressure of  
punching plate reinforcing screen: 0.1MPa

PART NO.	PART NAME	MATERIAL	REQ'D NO.	REMARKS
4	Gasket	T#1804-NA	1	
3	Screen	SUS304	1	Mesh
2	Cap	ASTM A216 WCB	1	
1	Body	ASTM A216 WCB	1	

BILL OF MATERIAL

**WASINO KIKI CO., LTD.**

MODEL	Y800WCBS-H	△			
NAME	Y-TYPE STRAINER	△			
DATE	20, Jan, 2011	SCALE	△		
APPROVED	Y, S	CHECKED	Y, S	NO.	DESCRIPTION
DESIGN		DRAWN	M, H	DWG.NO.	REV.
				SYL051B-1	